

MESTM
LIGHTING. CONTROLS. ENERGY.



MATRIX LED
SOLUTIONS INC.

PRODUCT CATALOG 2023





MATRIX LED SOLUTIONS

Welcome to Matrix LED Lighting Solutions, a leading provider of commercial LED lighting solutions in the Midwest. We specialize in providing high-quality LED lighting products and services to businesses of all sizes, helping them save energy and reduce costs while improving the lighting quality of their premises. At Matrix LED Lighting Solutions, we understand the importance of having the right lighting in your commercial space. That's why we offer a wide range of LED lighting products, including panel lights, tube lights, high bays, and flood lights, among others, to meet your specific lighting needs.

Our products are designed to provide maximum energy efficiency and longevity, ensuring that your investment pays off in the long run. Our team of experienced professionals is committed to providing exceptional customer service, from product selection to installation and maintenance. We work closely with our clients to understand their unique needs and provide tailored solutions that meet their specific requirements.

We pride ourselves on delivering reliable and high-quality products and services that exceed our clients' expectations. At Matrix LED Lighting Solutions, we are dedicated to promoting sustainable and eco-friendly practices by providing energy-efficient LED lighting solutions that help reduce carbon footprints. We believe in making a positive impact on our planet and helping our clients do the same. Thank you for considering Matrix LED Lighting Solutions as your LED lighting provider in the Midwest. Contact us today to learn more about how we can help you achieve your lighting goals.





Our Strategic Partnerships



TABLE OF CONTENTS

What's New	Pg. 6
Indoor Retrofit	Pg. 9
Outdoor Retrofit	Pg. 15
Indoor Fixtures	Pg. 19
High Bay Fixtures	Pg. 27
Outdoor Fixtures	Pg. 33
Tenons & Mounts	Pg. 52
Emergency Drivers	Pg. 54
Stand Alone Controls	Pg. 55
Network Lighting Controls	Pg. 56
Refrigeration	Pg. 60
Solar	Pg. 64



Matrix strives to stay at the forefront of LED lighting innovations, with an emphasis on quality and efficiency. We're excited to offer new products that are either sensor-ready, CCT Tunable, watt-selectable and more!

Our aim is to provide your business w/ cost-effective, energy-efficient lighting, designed for easy install and control, capable of adding a touch of beauty to any environment for years to come. Our standard **7-Year Warranty** will provide a higher level of quality assurance and value in every lighting category.

As you take a peek inside, we hope you like what you see. When you're ready to order, remember we're just a click away at Matrixledsolutionsinc.com or just a phone call away at **630.293.7338**.

New and Notable Products



Pine SSR+
LED High Strip Body

- Wattage Selectable
- Dimmable
- ZSR Ready for NLC controls
- 10 KV Surge Protection
- 155 LM/W

P. 30



ASH GSR+
LED Round High Bay

- Wattage Selectable
- CCT Tunable
- Dimmable
- ZSR Ready for NLC controls
- 6 KV Surge Protection
- 155 LM/W

P. 27



Wolf GSR
LED Area Light

- Wattage Selectable
- CCT Tunable
- Dimmable
- ZSR Ready for NLC controls
- 10 KV Surge Protection
- 155 LM/W

P. 45



Cougar S
LED STREET LIGHT

- Wattage Selectable
- Dimmable
- Built In Photocell
- 10 KV Surge Protection
- Convert into Area Light

P. 47



Puma G
LED Area Light

- Wattage Selectable
- CCT Tunable
- Dimmable
- Built In Photocell
- 6 KV Surge Protection
- 155 LM/W

P. 42



Hercules G
Led Canopy Fixture

- Wattage Selectable
- CCT Tunable
- Dimmable
- Sensor Ready for NLC controls
- 6 KV Surge Protection

P. 37



SPRUCE GSR+
LED BACKLIT THIN PANEL

- Wattage Selectable
- CCT Tunable
- Dimmable
- Sensor Ready for NLC controls

P. 22



Iris
LED Magnetic Strip Retrofit

- Wattage Selectable
- Dimmable
- Sensor Ready for NLC controls
- 160 LM/W

P. 11



Coyote SSR
LED SPORTS LIGHT

- Wattage Selectable
- Dimmable
- ZSR Ready for NLC controls
- 20 KV Surge Protection
- Remote Driver
- 155 LM/W

P. 50



Bengal G
Led Dusk to Dawn

- Wattage Selectable
- CCT Tunable
- Dimmable
- Photocell Ready

P. 36



Bobcat
LED Soffit Canopy Fixture

- Wattage Selectable
- CCT Tunable
- Dimmable
- Sensor Ready for NLC controls
- Available Bronze & White

P. 18



Bollard
LED

- Wattage Selectable
- CCT Tunable
- Dimmable
- Available in Bronze & White
- Available in Round & Square

P. 48



Leopard G
LED Post Top

- Wattage Selectable
- CCT Tunable
- Dimmable
- Photocell Ready
- Convert into Area Light
- 155 LM/W

P. 49



MES GLOSSARY

Look for the following features on our line of products:



Selectable Wattage

Products with the Selectable Wattage badge offer energy-efficient cost-saving solutions by allowing users the ability to quickly decrease or increase the LED wattage.



Correlated Color Temperature (CCT) Tunable

MES products with the CCT Tunable badge have the ability to deliver varying light color from 3000K to 5000K.



ZSR Sensor Ready Technology

Our ZSR Sensor Ready Technology badge indicates that this product provides an optimal lighting solution in seconds with the ability to add a wide array of control devices to your fixture.



Sensor Ready

MES products with the Sensor Ready badge come with designated receptacles allowing quick and convenient sensor plug in.



Dimmable

The Dimmable symbol denotes MES products with dimming capabilities.



High Lumen

These products emit brighter light, making them ideal for large indoor and outdoor spaces where a lot of light is required.



Photocell

Fixtures with built-in Photocell



Dark Sky Compliant

Fixture light beam is angle down to prevent light trespass



Light Linq

An intelligent network of individually addressable lights and control devices that allows each device to send and receive data.



SkyFi Blu+

No gateway or Internet needed. Safe and easy installation. Wireless Bluetooth mesh connection. Area/Group control & linking



MES Standard 7-Year Product Warranty

MES fixtures come standard with a best-in-class 7-year warranty.



MES Optional 10-Year Product Warranty

MES offers an optional 10-year warranty for products and labor.

MODEL DESCRIPTIONS

MODEL	TIER	DESCRIPTION
B	Bronze	Single wattage, Single CCT, Non-Sensor Ready
BSR	Bronze SR	Single wattage, Single CCT, Sensor Ready
BWS	Bronze WS	Single wattage, Single CCT, with Sensor
S	Silver	Selectable Wattage or CCT Tunable, Non-Sensor Ready
SSR	Silver SR	Selectable Wattage or CCT Tunable, Sensor Ready
SWS	Silver WS	Selectable Wattage or CCT Tunable, with Sensor
G	Gold	Selectable Wattage and CCT Tunable, Non-Sensor Ready
GSR	Gold SR	Selectable Wattage and CCT Tunable, Sensor Ready
GWS	Gold WS	Selectable Wattage and CCT Tunable, with sensor

IP RATINGS

IP ratings featured on our line of products:



IP20

MES products w/ this rating are protected against being touched by hand or large tools.



IP44

MES products w/ this rating offer protection against invasive small objects larger than 1mm, such as a wire, and protected against splashes of water projected from any direction.



IP54

MES products w/ this rating are protected against dust and splashes of water from any direction.



IP64

MES products w/ this rating are dust-resistant and protected against splashes of water from any direction.



IP65

MES products w/ this rating are dust-resistant and protected against jets of water projected from any direction.



IP67

MES products w/ this rating are dust-resistant and fully protected against immersion in water for 30 minutes to a depth of 1 meter.

CERTIFICATIONS



For more than 100 years, Underwriters Laboratories has been non-profit organization dedicated to public safety. UL sets standards for different product categories and tests products to make sure they meet the standards.

The ETL Mark is proof of product compliance to North America safety standards. Authorities Having Jurisdiction (AHJs) and code officials across the US and Canada accept ETL Listed Mark as proof of product compliance to published industry standards.

To see MES products in this catalog that meet UL or ETL standards, look for the UL or ETL badge.

DesignLights Consortium®

The DesignLights Consortium (DLC) is a non-profit organization promoting high-quality, energy-efficient lighting products in collaboration w/ utilities and energy-efficiency program members, manufacturers, lighting designers, and federal, state and local entities.

To find MES products in this catalog that meet DLC standards, look for the DLC badge.



LED TYPE A, B, A+B TUBES


Description:
LED Type A, B, A+B tubes are ideal for customers with older fluorescent ballasts who want to maximize efficiency with high system efficacy, guaranteed system compatibility, and the greatest overall performance.

- Features:**
- Frosted glass; eliminates pixelation
 - Instant startup
 - Suitable for retail, schools, offices, healthcare and other various commercial applications



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Tube Type	Size	Watts	CCT	LM/Watts	Total LM	Voltage	Color	
09230	PQLGVYFU	Type B	Dual End	2FT	6W	4000K	150 LM/W	120-277V	White	
09231	PRPF5H8T			2FT	6W	5000K				900 LM
09232	POSNMKKG		Bypass	4FT	9W	4000K	177 LM/W			1,350 LM
09233	P9IT03CA			4FT	9W	5000K				1,350 LM
09234	PRW7790B	Type A+B	Dual Mode	4FT	9W	4000K	177 LM/W	120-277V	White	
09235	PXPQDJHL			4FT	9W	5000K				1,350 LM
02081	PQLGVYFU		Dual Mode	4FT	15W	4000K	150 LM/W			2,250 LM
02082	PRPF5H8T			4FT	15W	5000K				2,250 LM



LED TYPE C TUBES RETROFIT (ORCHARD B & BSR)

Description:
Our External Drive LED Type C tubes are ideal for customers with older fluorescent ballasts who want to maximize efficiency, but don't want to install Type B linear voltage retrofit lamps. Our External Drive LED system can be integrated with robust dimming and control functionality. Our Type C LED tubes offer high system efficacy, guaranteed system compatibility, and the greatest overall performance.

- Features:**
- Frosted glass; eliminates pixelation
 - Instant startup
 - Suitable for retail, schools, offices, healthcare and other various commercial applications




[Click Here For Full Spec](#)

Order Code	DLC Product ID	Number of Tubes	Watts	CCT	LM/Watts	Total LM	Voltage	Color
13965	PYYFLQ67	1 Tube	13W	4000K	140 LM/W	1,820 LM	120-277V	White
13966	PHJ0BOQR	1 Tube	13W	5000K		1,820 LM		
13967	PS4JC44S	1 Tube	15W	4000K		2,100 LM		
13968	PBTMYMBR	1 Tube	15W	5000K		2,100 LM		
13969	PYETK1LT	2 Tube	26W	4000K		3,640 LM		
13970	PYSTXTFF	2 Tube	26W	5000K		3,640 LM		
13971	POHF1TTU	2 Tube	30W	4000K		4,200 LM		
13972	PRJZO8M7	2 Tube	30W	5000K		4,200 LM		
13973	BRBGST0	4 Tube	52W	4000K		7,280 LM		
13974	PYMBJQKN	4 Tube	52W	5000K		7,280 LM		
13975	PW5C7PIQ	4 Tube	60W	4000K		8,400 LM		
13976	PXGCBLLP	4 Tube	60W	5000K		8,400 LM		

LIGHTING CONTROLS

Order Code	Description
06210	LED 3 in 1 OcuSense Indoor Fixture Embedded with Detachable Sensor White Gen 2
06267	DC Powered 3 in 1 Indoor OcuSense Stand-Alone Control Quick Connect Sensor Ready Fixtures
06278	Remote Control 1 Scene Programming with LCD Display White Gen 2
06261	BLE PIR Fixture Mounted (SkyFi Blu+) Occupancy Sensor w/ Daylight Harvesting 40ft 100-277V Type D
06274	DC Powered BLE OcuSense (LightLinQ) Occ Control w/ Daylight Harvesting White 17ft For Quick Connect SR Fixtures



LED MAGNETIC STRIP RETROFIT (IRIS)

Description:

The Magnetic Strip Retro series is a family of LED Magnetic retrofit kits, which are used to update existing 2x2 and 2x4 fluorescent luminaires to LED. This family of retrofit also simplifies installation: simply replace your fluorescent tubes with the Magnetic Strips and the fixture's ballast with the included high-performance LED driver. Installation can be completed in as little as 5 minutes. These kits includes LED Strips, an external driver, a connector, and attached magnets for a quick install

Features:

- LED strips, LED drivers, connector
- Suitable for retail, schools, offices, healthcare, and other various commercial applications

[Click Here For Full Spec](#)



Order Code (No Lens)	Order Code (Frosted)	DLC Product ID	Wattage	Strip Count	CCT	LM/Watt	Total LM	Voltage
----------------------	----------------------	----------------	---------	-------------	-----	---------	----------	---------

4' Magnetic Strips

10126	10282	S-UZW035	60W	2 Strip	3500K	160 LM/W	9,600 LM	120 - 277 V
10127	10283	S-XDUKZO	60W	2 Strip	4000K		9,600 LM	
10128	10284	S-XY04LG	60W	2 Strip	5000K		9,600 LM	
10129	10285	S-GF4VX2	80W	2 Strip	3500K		12,800 LM	
10130	10286	S-NMAFHK	80W	2 Strip	4000K		12,800 LM	
10131	10287	S-ZKLP53	80W	2 Strip	5000K		12,800 LM	

LIGHTING CONTROLS

Order Code	Description
06210	LED 3 in 1 OcuSense Indoor Fixture Embedded with Detachable Sensor White Gen 2
06267	DC Powered 3 in 1 Indoor OcuSense Stand-Alone Control Quick Connect Sensor Ready Fixtures
06278	Remote Control 1 Scene Programming with LCD Display White Gen 2
06261	BLE PIR Fixture Mounted (SkyFi Blu+) Occupancy Sensor w/ Daylight Harvesting 40ft 100-277V Type D
06274	DC Powered BLE OcuSense (LightLinq) Occ Control w/ Daylight Harvesting White 17ft For Quick Connect SR Fixtures

Order Code (No Lens)	Order Code (Frosted)	DLC Product ID	Wattage	Strip Count	CCT	LM/Watt	Total LM	Voltage
----------------------	----------------------	----------------	---------	-------------	-----	---------	----------	---------

2' Magnetic Strips

10081	10237	S-09P746	15W	1 Strip	3500K	160 LM/W	3,200 LM	120 - 277 V
10082	10238	S-1US020	15W	1 Strip	4000K		3,200 LM	
10083	10239	S-2PB8DJ	15W	1 Strip	5000K		3,200 LM	
10093	10249	S-Q5LCIP	30W	2 Strip	3500K		4,800 LM	
10094	10250	S-43AZ92	30W	2 Strip	4000K		4,800 LM	
10095	10251	S-QJKOAD	30W	2 Strip	5000K		4,800 LM	
10096	10252	S-47P8N9	30W	3 Strip	3500K		4,800 LM	
10097	10253	S-4M9P8K	30W	3 Strip	4000K		4,800 LM	
10098	10254	S-54CET8	30W	3 Strip	5000K		4,800 LM	
10099	10255	S-ZBMF8S	40W	3 Strip	3500K		6,400 LM	
10100	10256	S-0HE4GS	40W	3 Strip	4000K	6,400 LM		
10101	10257	S-FLSI09	40W	3 Strip	5000K	6,400 LM		

4' Magnetic Strips

When placing your, please use Order Code.

10108	10264	S-8EM4FL	15W	1 Strip	3500K	160 LM/W	2,400 LM	120 - 277 V
10109	10265	S-8FR9VZ	15W	1 Strip	4000K		2,400 LM	
10110	10266	S-AGJ04M	15W	1 Strip	5000K		2,400 LM	
10111	10267	S-0MEHZ8	24W	1 Strip	3500K		3,840 LM	
10112	10268	S-D61GE4	24W	1 Strip	4000K		3,840 LM	
10113	10269	S-E8CVL6	24W	1 Strip	5000K		3,840 LM	
10117	10273	S-0MEHZ8	24W	2 Strip	3500K		3,840 LM	
10118	10274	S-D61GE4	24W	2 Strip	4000K		3,840 LM	
10119	10275	S-E8CVL6	24W	2 Strip	5000K		3,840 LM	
10120	10276	S-SHN43W	30W	2 Strip	3500K		4,800 LM	
10121	10277	S-LQRCZK	30W	2 Strip	4000K	4,800 LM		
10122	10278	S-0EX8K4	30W	2 Strip	5000K	4,800 LM		
10123	10279	S-64EB50	40W	2 Strip	3500K	6,400 LM		
10124	10280	S-2K7U8X	40W	2Strip	4000K	6,400 LM		
10125	10281	S-H3IV75	40W	2 Strip	5000K	6,400 LM		
10138	10294	S-F6Y7TB	45W	3 Strip	3500K	7,200 LM		
10139	10295	S-J60LG1	45W	3 Strip	4000K	7,200 LM		
10140	10296	S-AXVZ8B	45W	3 Strip	5000K	7,200 LM		
10141	10297	S-ZXLS40	60W	3 Strip	3500K	9,600 LM		
10142	10298	S-YL8KT5	60W	3 Strip	4000K	9,600 LM		
10143	10299	S-4I150Z	60W	3 Strip	5000K	9,600 LM		
10150	10306	S-UZW035	60W	4 Strip	3500K	9,600 LM		
10151	10307	S-XDUKZO	60W	4 Strip	4000K	9,600 LM		
10152	10308	S-XY04LG	60W	4 Strip	5000K	9,600 LM		
10153	10309	S-GF4VX2	80W	4 Strip	3500K	12,800 LM		
10154	10310	S-NMAFHK	80W	4 Strip	4000K	12,800 LM		
10155	10311	S-ZKLP53	80W	4 Strip	5000K	12,800 LM		

LED STRIP FIXTURE RETROFIT (LILY S & G)

Description:

Our Strip Fixture Retrofit (SFR) kit includes everything needed for a seamless quick retrofit of existing 4' and 8' fluorescent strips along with other industrial fixtures to LED, in as little as two minute. It's the industry's fastest LED strip retrofit kit!. The SFR includes housing with pre-wired drivers, installation brackets, lenses, and hardware with each retrofit kit.

Features:

- AL+PC with an acrylic lens, removable for quick cleaning
- Suitable for retail, schools, offices, healthcare, and other various commercial applications




[Click Here For Full Spec](#)

Order Code	DLC Product ID	Size	Watts	CCT	LM/Watt	Total LM	Voltage	Color
04007	S-HKWA9M	4FT	34W 38W 45W	5000K	135 LM/W	4,590 LM 5,130 LM 6,075 LM	120 - 277V	White
04008	S-HKWA9M	4FT	34W 38W 45W	3500K 4000K 5000K		4,590 LM 5,130 LM 6,075 LM		
04005	S-KC8FRP	8FT	38W 46W 54W	5000K		5,130 LM 6,210 LM 7,290 LM		
04006	S-KC8FRP	8FT	38W 46W 54W	3500K 4000K 5000K		5,130 LM 6,210 LM 7,290 LM		
04009	S-G2LU47	8FT	65W 75W 90W	5000K		8,775 LM 10,125 LM 12,150 LM		

LIGHTING CONTROLS

Order Code	Description
06247	LED PIR Fixture Mounted Control Simple On/Off 39FT 120-347V Type D Connector White
06246	LED PIR Fixture Mounted Control 3 in 1 39FT 120-347V Type D Connector White
06278	Remote Control 1 Scene Programming with LCD Display White
06261	BLE PIR Fixture Mounted (SkyFi Blu+) Occupancy Sensor w/ Daylight Harvesting 40ft 100-277V Type D
06265	BLE Fixture Mounted Node (SkyFi Blu+) 120-277V Type D (MES)



LED VOLUMETRIC TROFFER RETROFIT (LILAC GSR)

Description:

The Slim Line LED retrofit kit for troffers simplifies the conversion from existing fluorescent 2x2 and 2x4 recessed troffer fixtures to energy efficient LED fixtures using the back housing of the existing fixture. This Troffer Retrofit kit can be retrofitted into most existing troffers in less than 15 minutes.

Features:

- Can be retrofitted into most existing troffers.
- Continuous dimming (0-10V) comes standard.
- Suitable for retail, schools, and other commercial applications



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Size	Watts	CCT	LM/Watt	Total LM	Voltage	Color			
04064	S-YZGL1E	1X4	20W 25W 30W	3500K 4000K 5000K	125 LM/W	2,500 LM 3,125 LM 3,750 LM	120 - 277V	White			
04065	S-Z1FVQP	2X2									
04066	S-MZI570	2X4							25W 30W 35W	128 LM/W	3,200 LM 3,840 LM 4,480 LM
04067	S-V0KHFY	2X4							34W 38W 45W	125 LM/W	4,250 LM 4,750 LM 5,625 LM

LIGHTING CONTROLS

Order Code	Description
06267	LDC Powered 3 in 1 Indoor OcuSense Stand-Alone Control For Quick Connect Sensor Ready Fixtures Control 1 Scene
06278	Remote Control 1 Scene Programming with LCD Display White
06274	DC Powered BLE OcuSense (LightLinq) Occ Control w/ Daylight Harvesting White 17ft For Quick





HID POST TOP RETROFIT

Description:

Our LED HID post top 360°retrofits are perfect for retrofitting your post top fixtures while providing 360° of high output LED light. These retrofit options are UL listed and enclosed fixture rated. With a reversible E39 mogul base, you can have either up or down light. Replace your metal halide lamps in your post top fixtures today with these beautiful LED replacements in 30 or 60 watts, available in 4000K or 5000K color temperature (CCT).

Features:

- E39 Mogul Base, die cast aluminum body with white finish Suitable for warehouses, gymnasiums, shopping centers



[Click Here For Full Spec](#)

Order Code	Description	Wattage	CCT	Voltage	Base	Lens
04425	LED Post Top HID Retrofit	30W	4000K	120-277V	E39 Base	Clear
04426	LED Post Top HID Retrofit	30W	5000K		E39 Base	Clear
04427	LED Post Top HID Retrofit	60W	4000K		E39 Base	Clear
04428	LED Post Top HID Retrofit	60W	5000K		E39 Base	Clear



HID OUTDOOR RETROFIT KIT WITH EXTERNAL DRIVER (TULIP B)

Description:

This Outdoor Retrofit Kit is a multi-function retrofit solution for commercial and outdoor fixtures. Replace old metal halide fixtures with this LED retrofit kit and get up to 130 lumens per watt for better energy efficiency. The fixture can be mounted horizontal or vertical, and can be used to retrofit HID wall packs, shoebox area lights and flood lights, canopy lights, and high bays. Simply remove your old bulb, bypass the ballast, and mount the retrofit kit inside your fixture with the included bracket mount and hardware.

Features:

- Heavy duty one-piece die cast aluminum heat sink with an integral thermal control sensor with external Meanwell driver
- Retrofit: wall pack shoebox, flood light, canopy, high bay



[Click Here For Full Spec](#)

Order Code	Description	Watts	CCT	LM/Watts	Total LM	Voltage	Color
06012	PNEAK3HH	35W	5000K	105 LM/W	3,675 LM	120-277V	Black
06005	PU9JP1EV	80W		124 LM/W	9,920 LM		
06013	P9017XPI	100W		127 LM/W	12,700 LM		
06008	PO4DZIO0	150W		130 LM/W	19,500 LM		
06009	PO4DZIO0	200W		119 LM/W	23,800 LM		
06010	PSTA2983	240W		126 LM/W	30,240 LM		



LED SOFFIT CANOPY RETROFIT (JASMINE S)

Description:

This slim and sleek LED Petroleum Canopy Light is a high performance fixture, capable retrofitting any soffit or canopy. Because of its unique design and features, it's the best outdoor lighting fixture applicable to any industrial or commercial premise but most particularly for gas stations. The 120-degree beam angle is perfect for illuminating large spaces without leaving dark spots. Comes with 12, 15, 18 inch plates in bronze or white making it versatile for all applications.

Features:

- Die cast aluminum with integral heat sink
- Suitable for warehouse, factory, gas station, soffit, workshop

[Click Here For Full Spec](#)

1. Choose fixture

2. Select plate size/color needed



Order Code	DLC Product ID	Watts	CCT	LM/Watt	Total LM	Voltage	Color
06100	S-OZAKDL	20W 30W 40W	5000K	140 LM/W	2,800 LM 4,200 LM 5,600 LM	120 - 277V	White

PLATES

Order Code	Description	CCT	Color
06122	LED Soffit Canopy Retrofit Plate	12x12	Bronze
06116	LED Soffit Canopy Retrofit Plate	15x15	Bronze
06117	LED Soffit Canopy Retrofit Plate	18x18	Bronze
06118	LED Soffit Canopy Retrofit Plate	12x12	White
06119	LED Soffit Canopy Retrofit Plate	15x15	White
06120	LED Soffit Canopy Retrofit Plate	18x18	White
06121	LED Soffit Canopy Retrofit Plate	22x22	White



LED SOFFIT CANOPY FIXTURE (BOBCAT G)

Description:

Designed to be used in moisture-filled or harsh settings, these fixtures have a durable housing that resists warping, fading, corrosion, and rust. The impact resistant lenses are able to withstand the weather, and are held in place by non-corrosive metal clips. LED vapor tight fixtures use half the energy of fluorescents, lowering energy cost. These fixtures also eliminate lamp replacement costs and compatibility issues by using integrated LEDs.

Features:

- Capable of retrofitting any Soffit or Canopy.
- 120-degree beam angle is perfect for illuminating large spaces without leaving dark spots.
- Suitable for damp locations.

[Click Here For Full Spec](#)



Order Code	DLC Product ID	Watts	CCT	LM/Watt	Total LM	Voltage	Color	
06102	S-MNXDUL	13W 15W 20W	3500K 4000K 5000K	126 LM/W	1,638 LM 1,890 LM 2,520 LM	120-277V	White	
06103	S-DQVRCW	36W 45W 55W		121 LM/W	4,356 LM 6,655 LM 6,655 LM		White	
06104	S-MNXDUL	13W 15W 20W		126 LM/W	1,638 LM 1,890 LM 2,520 LM		Bronze	
06105	S-DQVRCW	36W		121 LM/W	4,356 LM		6,655 LM	Bronze
		45W 55W			6,655 LM			





LED VAPOR TIGHT FIXTURE (HAZEL GSR)

Description:

Designed to be used in moisture-filled or harsh settings, these fixtures have a durable housing that resists warping, fading, corrosion, and rust. The impact resistant lenses are able to withstand the weather, and are held in place by non-corrosive metal clips. LED vapor tight fixtures use half the energy of fluorescents, lowering energy cost. These fixtures also eliminate lamp replacement costs and compatibility issues by using integrated LEDs.

[Click Here For Full Spec](#)



Order Code	DLC Product ID	Watts	CCT	LM/Watt	Total LM	Voltage	Color
02508	S-TF1SHN	35W 45W 60W	3500K 4000K	140 LM/W	4,900 LM 6,300 LM 8,400 LM	120 - 277V	White
02509	S-6807H1	55W 65W 75W 90W	5000K		7,700 LM 9,100 LM 10,500 LM 12,600 LM		



LED VAPOR TIGHT HIGHBAY (HAZEL GSR)

Description:

Designed to be used in moisture-filled or harsh settings, these fixtures have a durable housing that resists warping, fading, corrosion, and rust. The impact resistant lenses are able to withstand the weather, and are held in place by non-corrosive metal clips. LED vapor tight fixtures use half the energy of fluorescents, lowering energy cost. These fixtures also eliminate lamp replacement costs and compatibility issues by using integrated LEDs.

[Click Here For Full Spec](#)



Order Code	DLC Product ID	Watts	CCT	LM/Watt	Total LM	Voltage	Color
02510	S-PQ1J60	105W 135W 155W 180W	3500K 4000K 5000K	140 LM/W	16,800 LM 19,600 LM 22,400 LM 25,200 LM	120-277V	White



LED COVERED STRIP FIXTURE (JUNIPER GSR)

Description:

The LED Covered Strip Fixture, available in 4' and 8', is designed as a direct replacement for fluorescent strips. This luminaire delivers general ambient lighting in a variety of indoor settings, including schools, offices, hospitals and stores, and is the perfect choice for both new construction and retrofits. This luminaire provides long-life and uniform illumination, as well as standard 0-10VDC dimming capability.

[Click Here For Full Spec](#)




Order Code	DLC Product ID	Size	Watts	CCT	LM/Watt	Total LM	Voltage	Color
02381	S-Z3AXC6	4FT	24W 32W 40W	3500K 4000K 5000K	130LM/W	3,120 LM 4,160 LM 5,200 LM	120-277V	White
02382	S-X8Z2FT	8FT	40W 50W 64W			5,200 LM 6,500 LM 8,450 LM		

LIGHTING CONTROLS (For Hazel and Juniper)

Order Code	Description
06247	LED PIR Fixture Mounted Control Simple On/Off 39FT 120-347V Type D Connector White
06246	LED PIR Fixture Mounted Control 3 in 1 39FT 120-347V Type D Connector White
06278	Remote Control 1 Scene Programming with LCD Display White
06261	BLE PIR Fixture Mounted (SkyFi Blu+) Occupancy Sensor w/ Daylight Harvesting 40ft 100-277V Type D
06265	BLE Fixture Mounted Node (SkyFi Blu+) 120-277V Type D (MES)





LED VOLUMETRIC TROFFER (REDWOOD FAMILY)

Description:
Our Redwood SSR troffer is dimmable, has selectable wattage and comes sensor ready. Our troffers provide a quick and easy solution for warehouse and other commercial applications. Available in 2’x2’ and 2’x4’ versions.

- Features:**
- Mountable in an existing troffer fixture
 - Durable steel housing with an acrylic lens that is removable for quick cleaning
 - Suitable for retail, schools, offices, healthcare and other various commercial applications



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Size	Watts	CCT	LM/Watt	Total LM	Voltage	Color
02665	P2XKSPNW	2X2	15W	4000K	133 LM/W	1,978 LM	120-277V	White
	PDTUL1MA		20W		134 LM/W	2,613 LM		
	P7K95S8R		30W		130 LM/W	3,591 LM		
02666	P6S7BN85	2X2	15W	5000K	133 LM/W	1,978 LM	120-277V	White
	PDUFZQYD		20W		134 LM/W	2,613 LM		
	PBKDMFSE		30W		130 LM/W	3,591 LM		
02667	PF4BSNSH	2X4	23W	4000K	135 LM/W	3,107 LM	120-277V	White
	P4JMJLTK		30W		132 LM/W	4,025 LM		
	PNLC2L16		40W		128 LM/W	5,138 LM		
02668	PWDSZHCF	2X4	23W	5000K	135 LM/W	3,107 LM	120-277V	White
	PE98PNUP		30W		132 LM/W	4,025 LM		
	PLAMLXYJ		40W		128 LM/W	5,138 LM		



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Size	Watts	CCT	LM/Watt	Total LM	Voltage	Color
02665	P7K95S8R	2X2	15W	3500K 4000K 5000K	133 LM/W	1,995 LM	120-277V	White
			20W		134 LM/W	2,680 LM		
			30W		130 LM/W	3,900 LM		
02666	PLOPLWQ6CX8T	2X2	30W	3500K 4000K 5000K	135 LM/W	4,050 LM	120-277V	White
			40W		132 LM/W	5,280 LM		
			50W		130 LM/W	6,500 LM		

LIGHTING CONTROLS

Order Code	Description
06267	LDC Powered 3 in 1 Indoor OcuSense Stand-Alone Control For Quick Connect Sensor Ready Fixtures Control 1 Scene
06278	Programming with LCD Display White
06274	DC Powered BLE OcuSense (LightLinQ) Occ Control w/ Daylight Harvesting White 17ft For Quick Connect SR Fixtures



LED BACKLIT THIN PANEL (SPRUCE GSR+)

Description:
Ideal for drop ceilings and easy to surface or suspension mount. Direct backlit design provides a smooth and more uniform light distribution than edge-lit panels. Our most common replacement for 2x2 or 2x4 drop ceiling grids where conventional fluorescent troffers are commonly used.

- Features:**
- High-grade aluminum housing, zinc-coated iron back cover
 - Suitable for offices, conference rooms, schools & other commercial applications



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Size	Watts	CCT	LM/Watt	Total LM	Voltage	Color
02838	PLYIUCDY7TUR	1X4	20W	3000K 3500K 4000K 5000K 6500K	125 LM/W	2,500 LM	120 - 277V	White
			30W			3,750 LM		
			40W			5,500 LM		
02839	PLRT9IOZV3FY	2X2	20W	3000K 3500K 4000K 5000K 6500K	125 LM/W	2,500 LM	120 - 277V	White
			30W			3,750 LM		
			40W			5,500 LM		
02840	PAY7VNAN	2x4	23W	3000K 3500K 4000K 5000K 6500K	125 LM/W	2,875 LM	120 - 277V	White
			30W			3,750 LM		
			40W			5,500 LM		
02841	PLOPLWQ6CX8T	2x4	30W	3000K 3500K 4000K 5000K 6500K	125 LM/W	3,750 LM	120 - 277V	White
			40W			5,500 LM		
			50W			6,250 LM		


ACCESSORIES

Order Code	Description
02880	1x4 Flat Panel - Surface Mount Brackets
02881	2x2 Flat Panel - Surface Mount Brackets
02882	2x4 Flat Panel - Surface Mount Brackets
02884	2x2 Recessed Flange For Drywall Ceilings
02885	2x4 Recessed Flange For Drywall Ceilings
02886	Aircraft Cable (Universal Yoke and Toggle Suspension Kit)

LIGHTING CONTROLS

Order Code	Description
06267	LDC Powered 3 in 1 Indoor OcuSense Stand-Alone Control For Quick Connect Sensor Ready Fixtures Control 1 Scene
06278	Programming with LCD Display White
06274	DC Powered BLE OcuSense (LightLinQ) Occ Control w/ Daylight Harvesting White 17ft For Quick Connect SR Fixtures

SMART FIXTURES



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Wattage	CCT	Voltage	Function	Color
02673	TPTMTR22CFLB-36WA	36W	3500K 4000K 5000K	120 - 277V	Bluetooth	White
02674	TPTMTR24CFLB-50WA	50W	6500K			



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Wattage	CCT	Voltage	Function	Color
02836	TPTMPD22CFLB-36WA	36W	3500K 4000K 5000K	120 - 277V	Bluetooth	White
02837	TPTMPD24CFLB-50WA	50W	6500K			



LED ARCHITECTURAL LINEAR STRIP LIGHT(ASPEN SSR)

Description:

This sleek, stylish light features up and down lighting, making this a highly effective lighting solution. These 4-foot LED direct/indirect suspended linear fixtures can be linked together are ideal for a variety of indoor and architectural applications where continuous linear lighting is desired. It is suitable for suspended mounting and can be used in continuous rows.

Features

- Steel housing and acrylic lens
- Suitable for hospitals, offices, schools, stores



[Click Here For Full Spec](#)

LED 4ft Architectural Linear Light (Up / Down)

Order Code	DLC Product ID	Size	Watts	CCT	LM/Watt	Total LM	Voltage	Color
02565	S-A4K532	4FT	30W	3500K	131 LM/W	3,930 LM	120-277V	White
02566	S-TK53QF		40W 50W	4000K 5000K		5,240 LM 6,550 LM		Black

Accessories

LED L Shape Architectural (Up / Down)

Order Code	Size	Wattage	CCT	LM/Watts	Voltage	Total LM	Color
02567	4FT	30W	3500K	131 LM/W	120-277V	3,930 LM	White
02568			4000K 5000K				Black

LED X Shape Architectural (Up / Down)

Order Code	Size	Wattage	CCT	LM/Watts	Voltage	Total LM	Color
02569	4FT	30W	3500K	131 LM/W	120-277V	3,930 LM 5,240 LM 6,550 LM	White
02570			4000K 5000K				Black

LIGHTING CONTROLS

Order Code	Description
06247	LED PIR Fixture Mounted Control Simple On/Off 39FT 120-347V Type D Connector White
06246	LED PIR Fixture Mounted Control 3 in 1 39FT 120-347V Type D Connector White
06278	Remote Control 1 Scene Programming with LCD Display White
06261	BLE PIR Fixture Mounted (SkyFi Blu+) Occupancy Sensor w/ Daylight Harvesting 40ft 100-277V Type D
06265	BLE Fixture Mounted Node (SkyFi Blu+) 120-277V Type D (MES)

Mounts - Needed to wall mount, suspend, or daisy chain together. See full spec sheet for the mounts order codes.



LED DOWNLIGHT (WILLOW G)

Description:

Our 4", 6", 8" and 10" LED commercial downlights are wattage selectable, CCT tunable and can be programmed with a toggle switch, allowing the ability to choose multiple color temperatures for any setting. Designed to meet most recessed downlighting application needs. This downlight offers comfortable, diffused lighting, with quiet & flicker-free LED technology.

Features:

- High-grade aluminum housing
- Suitable for offices, conference rooms, retail stores, health care facilities



[Click Here For Full Spec](#)

Order Code	Product #	Size	Watts	CCT	LM/Watt	Total LM	Voltage	Color
02938	MES-DL254-4-12W-OAC3B	4"	6W 8W 12W	3000K 4000K 5000K	106 LM/W	636 LM 848 LM 1,272 LM	120-277V	White
02939	MES-DL254-6-16W-OAC3A	6"	8W 12W 16W	3000K 3500K 5000K		960 LM 1,272 LM 1,696 LM		
02940	MES-DL254-6-16W-OAC3B	6"	8W 12W 16W	3000K 4000K 5000K		848 LM 1,272 LM 1,696 LM		
02941	MES-DL254-8-22W-OAC3A	8"	12W 16W 22W	3000K 3500K 5000K		1,272 LM 1,696 LM 2,332 LM		
02942	MES-DL254-8-22W-OAC3B	8"	12W 16W 22W	3000K 4000K 5000K		1,272 LM 1,696 LM 2,332 LM		
02943	MES-DL254-10-33W-OAC3A	10"	22W 28W 33W	3000K 3500K 5000K		2,332 LM 2,968 LM 3,498 LM		
02944	MES-DL254-10-33W-OAC3B	10"	22W 28W 33W	3000K 4000K 5000K		2,332 LM 2,968 LM 3,498 LM		

LIGHTING CONTROLS

Order Code	Description
06210	LED 3 in 1 OcuSense Indoor Fixture Embedded with Detachable Sensor White Gen 2
06278	Remote Control 1 Scene Programming with LCD Display White Gen 2
06265	BLE Fixture Mounted Node (SkyFi Blu+) 120-277V Type D




ZSR RECEPTACLE



PIR SENSOR



REMOTE CONTROL



ZSR SENSOR TECHNOLOGY?

It's the easiest way to add controls to illuminate fixtures. Our ZSR sensor ready technology provides an optimal lighting solution in seconds, delivering the quickest and safest route to add a wide array of control devices to your fixture.

INDUSTRY STANDARD

The ZSR receptacle is an industry standard interface for adding low voltage controls to 0-10V dimming fixtures. Look for the ZSR logo and you know your device is sensor ready and easy to control!



CONTROLS DEVICES

The ZSR receptacle works with a wide variety of control devices, including photocontrols, motion sensors, networked lighting controls including other third-party control devices identified as being compatible with ZSR.

Fixtures that include a ZSR interface work with controls that contain 3-in-1 functionality: Occupancy, Bi-Level Dimming, and Daylight Control. ZSR enabled fixtures provide plug- and-play controls functionality right out of the box.

LED ROUND HIGH BAY (ASH GSR+)



Description:

These sensor ready LED Round High Bays are the energy efficient, cost saving alternative to a traditional metal halide lights. These commercial low-profile high bay fixtures provide a quick and easy solution for warehouse and industrial applications. The low-profile height allows for efficient packaging, as well as accommodates applications where a low hanging fixture is undesirable.

Features:

- Heavy duty cast aluminum with an integrated thermally efficient heatsink profile
- Suitable for garage, gymnasium, parking garage, workshop
- Comes with 6ft cord



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Watts	CCT	LM/Watt	Total LM	Voltage	Color
03065-02	S-VEMO4W	60W 80W 100W	3500K 4000K 5000K	155 LM/W	9,300 LM 12,400 LM 15,500 LM	120-277V	Black
03066-02	S-BIV8AP	110W 130W 150W			17,050 LM 20,150 LM 23,250 LM		
03068-02	S-KCLWZG	200W 220W 240W			31,000 LM 34,100 LM 37,200 LM		
03080-02	S-KCLWZG	200W 220W 240W			31,000 LM 34,100 LM 37,200 LM		

ACCESSORIES

Order Code	Description	Wattage	Voltage
03045	LED Round High Bay Acrylic Reflector	100W-150W	-
03047	LED Round High Bay Surface Mount	100W-150W	-
03049	LED Round High Bay Wire Guard	100W-150W	-
09458	LED Round High Bay Pendant Mount	100W-150W	-
03044	LED Round High Bay Acrylic Reflector	200W-240W	-
03046	LED Round High Bay Surface Mount	200W-240W	-
03048	LED Round High Bay Wire Guard	200W-240W	-
09458	LED Round High Bay Pendant Mount	200W-240W	-

LED ROUND HIGH BAY (ASH SSR)



Description:

These sensor ready LED Round High Bay are the energy efficient, cost saving alternative to a traditional metal halide lights. These commercial low-profile high bay fixtures provide a quick and easy solution for warehouse and industrial applications. The low-profile height allows for efficient packaging, as well as accommodates applications where a low hanging fixture is undesirable.

Features:

- Heavy duty cast aluminum with an integrated thermally efficient heatsink profile
- Suitable for garage, gymnasium, parking garage, workshop
- Comes with 6ft cord



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Watts	CCT	LM/Watt	Total LM	Voltage	Color
03065	PX3FRHHN	60W 80W 100W	5000K	142 LM/W	8,520 LM 11,360 LM 14,200 LM	120-277V	Black
03066	PEW83YA2	110W 130W 150W		138 LM/W	15,180 LM 17,940 LM 20,700 LM		
03067	PRRF89SS	165W 180W 200W		139 LM/W	22,935 LM 25,020 LM 27,800 LM		
03068	PT4JX6QD	200W 220W 240W		141 LM/W	28,200 LM 31,020 LM 33,840 LM		
03069	PEW83YA2	110W 135W 150W		138 LM/W	15,180 LM 18,630 LM 20,700 LM	277-480V	
03070	PRRF89SS	165W 180W 200W		139 LM/W	22,935 LM 25,020 LM 27,800 LM		

LIGHTING CONTROLS ASH GSR+ & ASH SSR

Order Code	Description
06251	DC Powered 3 in 1 Indoor PIR Stand-Alone Control 40ft for 01 ZSR Fixtures
06278	Remote Control 1 Scene Programming with LCD Display White
06264	WH DC Powered BLE PIR (SkyFi Blu+) Occ Control w/ Daylight Harvesting White 40ft for 01 ZSR & Z10 Fixtures
06270	DC Powered BLE PIR (LightLinq) Occ Control w/ Daylight Harvesting White 40ft for All ZSR Fixtures

LED LINEAR HIGH BAY (PINE SSR)

Description:

These commercial linear high bay fixtures provide a quick and easy solution for warehouse and industrial applications. The linear profile allows for a one-for-one substitution with existing linear fluorescent high bay fixtures where the original chain suspension hardware can transfer directly over for an easy quick install. .

Features:

- Heavy duty cast aluminum with an integrated thermally efficient heatsink profile
- Suitable for garage, gymnasium, parking garage, workshop
- Aircraft cable and 6ft cord included



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Size	Watts	CCT	LM/Watt	Total LM	Voltage	Color
09240	P6TGD30M	2FT	70W	5000K	145 LM/W	10,150 LM	120-277V	White
	PU78BYBV		90W			12,780 LM		
	PGGTYDDB		110W			14,960 LM		
09241	PBG47YON	2FT	135W			18,225 LM		
	PR367EZJ		150W			20,850 LM		
	PYLZHQA8		165W			22,440 LM		
09242	PU3MC9U9	2FT	180W			25,560 LM		
	PSDZ4D7C		200W			28,000 LM		
	PO4NC2D6		220W			29,920 LM		
09243	PHESIEG5	3FT	180W			25,560 LM		
	PT7ZY8W3		200W			28,000 LM		
	PCD7VJSI		220W			29,920 LM		
09244	PM8IQGRL	3FT	255W	35,955 LM				
	PEG7O5QF		275W	37,400 LM				
	PALLZTQ9		300W	40,500 LM				

LIGHTING CONTROLS

Order Code	Description
06251	DC Powered 3 in 1 Indoor PIR Stand-Alone Control 40ft for 01 ZSR Fixtures
06278	Remote Control 1 Scene Programming with LCD Display White
06264	WH DC Powered BLE PIR (SkyFi Blu+) Occ Control w/ Daylight Harvesting White 40ft for 01 ZSR & Z10 Fixtures
06270	DC Powered BLE PIR (LightLinq) Occ Control w/ Daylight Harvesting White 40ft for All ZSR Fixtures

LED LINEAR HIGH BAY (PINE SSR+)

Description:

These commercial linear high bay fixtures provide a quick and easy solution for warehouse and industrial applications. The linear profile allows for a one-for-one substitution with existing linear fluorescent high bay fixtures where the original chain suspension hardware can transfer directly over for an easy quick install.

Light is soft and uniform, safe to eyes with Instant start, NO flickering, NO humming. Green and eco-friendly without mercury. ZSR Ready for quick sensor install Notable features are 135 degree beam adjustment and 5 Wattage Selectable.

Features:

- Heavy duty cast aluminum with an integrated thermally efficient heatsink profile
- Suitable for garage, gymnasium, parking garage, workshop
- Aircraft cable and 6ft cord included



[Click Here For Full Spec](#)

Order Coder	DLC Product ID	Size	Watts	CCT	LM/Watt	Total LM	Voltage	Color				
09240 - 03	S-BXIQWY	2FT	50W	5000K	160 LM/W	8,000 LM	120-277V	White				
			60W			9,600 LM						
			70W			11,200 LM						
			90W			14,400 LM						
09241 - 03	S-GNIPZJ	2FT	110W			17,600 LM						
			90W			14,580 LM						
			110W			17,820 LM						
			130W			21,060 LM						
09242 - 03	S-DSX36M	2FT	150W			5000K			160 LM/W	24,000 LM	277 - 480V	White
			165W							26,400 LM		
			180W							28,800 LM		
			200W							32,000 LM		
09245	S-GNIPZJ	2FT	220W	35,200 LM								
			90W	14,580 LM								
			110W	17,820 LM								
			130W	21,060 LM								
09246	S-DSX36M	2FT	150W	5000K	160 LM/W		24,000 LM	277 - 480V		White		
			165W				26,400 LM					
			180W				28,800 LM					
			200W				32,000 LM					
09246	S-DSX36M	2FT	220W			35,200 LM						

LED VAPOR TIGHT HIGH BAY (HAZEL GSR)

Description:

Designed to be used in moisture-filled or harsh settings, durable housing resists warping, fading, corrosion, and rust. Fully gasketed polycarbonate housing with captive stainless-steel latches. Can be mounted using cable suspension or surface mounting.

Features:

- Impact resistant lens
- Waterproof Luminance
- NEMA - 4X & IK10 Rated
- Eliminates pixelation
- Suitable for Gyms, warehouses, parking garages, and damp locations


[Click Here For Full Spec](#)



Order Code	DLC Product ID	Watts	CCT	LM/Watt	Total LM	Voltage	Color
02510	S-PQ1J60	105W 135W 155W 180W	3500K 4000K 5000K	140 LM/W	16,800 LM 19,600 LM 22,400 LM 25,200 LM	120-277V	White

LIGHTING CONTROLS

Order Code	Description
06247	LED PIR Fixture Mounted Control Simple On/Off 39FT 120-347V Type D Connector White
06246	LED PIR Fixture Mounted Control 3 in 1 39FT 120-347V Type D Connector White
06278	Remote Control 1 Scene Programming with LCD Display White
06261	BLE PIR Fixture Mounted (SkyFi Blu+) Occupancy Sensor w/ Daylight Harvesting 40ft 100-277V Type D
06265	BLE Fixture Mounted Node (SkyFi Blu+) 120-277V Type D (MES)



REMEMBER

MES OPTIONAL 10 YEAR WARRANTY



MES products come standard with a best-in-class 7-year warranty. For an additional peace of mind, remember to request our optional 10-year product warranty or 10-year warranty for product and labor.

See your sales representative for additional details.



LED SECURITY WALL PACK (CHEETAH G)

Description:

The Security Wall Pack is a great addition to poorly lit areas. This fixture can be mounted directly to a wall, side of building, or above a walkway. Construction consists of a weatherproof powder coated aluminum housing with wiring and conduit knockouts and a polycarbonate lens. Easily mount the wall pack on a recessed junction box. With its built in photocell, this fixture turns on automatically when the environment gets dark and turns off by itself with the first glimpse of daylight.

Features:

- Die-cast aluminum with prismatic polycarbonate lens
- Suitable for security lighting, perimeter lighting, parking garage
- Photocell included



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Watts	CCT	LM/Watt	Total LM	Voltage	Color
05059	S-0L6ZV8	10W	3500K 4000K 5000K	135 LM/W	1,350 LM	120 - 277V	Bronze
		15W			2,025 LM		
		20W			2,660 LM		
05058	S-0L6ZV8	10W	3500K 4000K 5000K	135 LM/W	1,350 LM	120 - 277V	White
		15W			2,025 LM		
		20W			2,660 LM		



LED STANDARD WALL PACK (TIGER B)

Description:

The LED standard wall pack combines traditional wall pack design with high-output LEDs to provide an energy-efficient, low maintenance LED wall pack suitable for replacing Metal Halide fixtures. The traditional shape helps maintain building aesthetics when replacing only a portion of your building's wall packs at a time while also eliminating unwanted markings from the removal of older fixtures.

Features:

- Die-cast aluminum housing with hinged door frame
- Suitable for warehouse, factory, storage, pedestrian lighting
- Photocell included



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Photocell	Wattage	LM/Watt	CCT	Total Lumen	Voltage	Color
05252	PLSZPP4F1ZUD	Yes	40W	135 LM/W	5000K	5,400 LM	120 - 277V	Bronze
05253	PLR6W6EYNNAC		60W			8,100 LM		Bronze
05251	PL7SDTDXTWI8		80W			10,800 LM		Bronze
05256	PLXREYAYY0AU		120W			16,200 LM		Bronze
09102	PLSZPP4F1ZUD		35W			4,725 LM		White
05257	PLR6W6EYNNAC		60W			8,100 LM		White
09104	PL7SDTDXTWI8		80W			10,800 LM		White
09229	PLXREYAYY0AU		120W			16,200 LM		White



Order Code	DLC Product ID	Wattage	LM/Watt	CCT	Total Lumen	Voltage	Color
05258	PLSZPP4F1ZUD	40W	135 LM/W	3500K	5,400 LM	120 - 277V	Bronze
05254	PLR6W6EYNNAC	60W		4000K	8,100 LM		Bronze
05255	PL7SDTDXTWI8	80W		5000K	10,800 LM		Bronze

LIGHTING CONTROLS

Order Code	Description
06261	BLE PIR Fixture Mounted (SkyFi Blu+) Occupancy Sensor w/ Daylight Harvesting 40ft 100-277V Type D
06265	BLE Fixture Mounted Node (SkyFi Blu+) 120-277V Type D



LED FULL CUTOFF WALL PACK (JAGUAR G)

Description:

The LED Full Cutoff Wall Pack (Jaguar G) is a sleek and energy-efficient lighting solution that provides superior illumination with minimal light pollution. Its innovative design ensures that all light is directed downward, making it an ideal choice for outdoor applications where glare reduction and dark sky compliance are important considerations.

Features:

- Night Sky Compliant
- Sealed with silicone to keep out dust and water
- Can be mounted directly to a wall, side of building, or above a walkway.
- Easily mount the wall pack on a recessed junction box.
- Built-in photocell



Order Code	DLC Product ID	Watts	CCT	LM/Watt	Total LM	Voltage	Color
05126	PLGHFB031G1X	40W	3000K	130 LM/W	5,200 LM	120V -277V	Bronze
		60W	4000K		7,800 LM		
		80W	5000K		10,400 LM		



LED DUSK-to-DAWN LIGHT (BENGAL G)

Description:

This slim and sleek LED Petroleum Canopy Light is a high-performance light fixture, capable of being mounted in any soffit/ canopy or even surface mounted. Because of its unique design and features, it's the best outdoor lighting fixture applicable to any industrial or commercial premise but most particularly for gas stations. The 120-degree beam angle is perfect for illuminating large spaces without leaving dark spots.

Features:

- Low maintenance
- Easy to install for retrofits and new construction
- Knock outs on all four sides
- Can be washed down



Order Code	DLC Product ID	Watts	CCT	LM/Watt	Total LM	Voltage	Color
05005	S-Y5J3G7	40W	3000K	140 LM/W	8,361 LM	120-277V	Silver
		50W	4000K				
		60W	5000k				



LED SLIM FULL CUTOFF

Description:

This LED Slim Full Cutoff Wall Pack comes with selectable wattage and is PIR sensor ready, adjustable from 0-90 degree angles and ideal for ideal for commercial outdoor buildings. It easily replaces any pre-existing wall pack fixture.

Features:

- Die-cast aluminum housing with prismatic lens
- Suitable for warehouse, factory, storage, pedestrian lighting




Order Code	DLC Product ID	Watts	CCT	LM/Watt	Total LM	Voltage	Color
05109	P3EWXYMW	20W	5000K	135 LM/W	2,700 LM	120-277V	Bronze
		40W			5,400 LM		
		60W			8,100 LM		
		80W			10,800 LM		

ACCESSORIES

Order Code	Description	Watts	Voltage
05030	Curve Metal Pipe for Barn Light Only	-	-
08361	Step Down Transformer	-	480V to 100-277V

LIGHTING CONTROLS

Order Code	Description
05714	Blue Twist Lock Photocell 100-277V UL Listed
06261	BLE PIR Fixture Mounted (SkyFi Blu+) Occupancy Sensor w/ Daylight Harvesting 40ft 100-277V Type D
06265	BLE Fixture Mounted Node (SkyFi Blu+) 120-277V Type D





LED CANOPY FIXTURE (HERCULES GSR)

Description:

Provides a broad, even distribution of light that can help to enhance visibility, safety, and security in outdoor areas. They are also designed to withstand harsh weather conditions, such as rain, wind, and extreme temperatures, making them a reliable lighting solution for outdoor spaces like gas stations, cold storage, food processing,

Features:

- Low maintenance
- Easy to install for retrofits and new construction
- Knock outs on all four sides
- Can be washed down



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Watt	CCT	LM/Watt	Total LM	Voltage	Color
05822	PL2F6ZV4HPJ4	100W 120W 150W	3000K 4000K 5000K	130 LM/W	13,000 LM 15,600 LM 19,500 LM	120-277V	White



LED PETROLEUM CANOPY LIGHT (LYNX B)

Description:

This slim and sleek LED Petroleum Canopy Light is a high-performance light fixture, capable of being mounted in any soffit/canopy or even surface mounted. Because of its unique design and features, it's the best outdoor lighting fixture applicable to any industrial or commercial premise but most particularly for gas stations. The 120-degree beam angle is perfect for illuminating large spaces without leaving dark spots.

Features:

- Die cast aluminum with integral heatsink
- Suitable for warehouse, factory, gas station, workshop



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Watts	LM/Watt	CCT	Total LM	Voltage	Color
05855	PLPOZNPFFF0H	120W	132 LM/W	5000K	15,840 LM	120V - 277V	White
05856	PL5IVWB20013	150W			19,800 LM		

ACCESSORIES

Order Code	Description	Size	Hole	Voltage
05880	Canopy Flat Plate	18x18	8x8 Square Hole	-
05882	Canopy Flat Plate	18x18	-	-
05883	Canopy Flat Plate	24x24	8x8 Square Hole	-
05884	Canopy Flat Plate	24x24	-	-
08361	Step Down Transformer	-	-	200-480V to 100-277V

LIGHTING CONTROLS

Order Code	Description
06247	LED PIR Fixture Mounted Control Simple On/Off 39FT 120-347V Type D Connector White
06246	LED PIR Fixture Mounted Control 3 in 1 39FT 120-347V Type D Connector White
06278	Remote Control 1 Scene Programming with LCD Display White
06261	BLE PIR Fixture Mounted (SkyFi Blu+) Occupancy Sensor w/ Daylight Harvesting 40ft 100-277V Type D
06265	BLE Fixture Mounted Node (SkyFi Blu+) 120-277V Type D (MES)

ACCESSORIES

Order Code	Description	Size	Hole	Voltage
05880	Canopy Flat Plate	18x18	8x8 Square Hole	-
05882	Canopy Flat Plate	18x18	-	-
05883	Canopy Flat Plate	24x24	8x8 Square Hole	-
05884	Canopy Flat Plate	24x24	-	-
08361	Step Down Transformer	-	-	200-480V to 100-277V

LIGHTING CONTROLS

Order Code	Description
06247	LED PIR Fixture Mounted Control Simple On/Off 39FT 120-347V Type D Connector White
06246	LED PIR Fixture Mounted Control 3 in 1 39FT 120-347V Type D Connector White
06278	Remote Control 1 Scene Programming with LCD Display White
06261	BLE PIR Fixture Mounted (SkyFi Blu+) Occupancy Sensor w/ Daylight Harvesting 40ft 100-277V Type D
06265	BLE Fixture Mounted Node (SkyFi Blu+) 120-277V Type D (MES)

LED CANOPY / GARAGE FIXTURE (KODIAK G)



Description:

Our Kodiak G Garage Canopy Fixture is CCT tunable, has selectable wattage and capable of being mounted in any soffit/canopy or even surface mounted. This fixture is applicable to any industrial or commercial premise, but perfectly suitable for garages and parking spaces.

Features:

- 0-10V dimming.
- Die cast aluminum with integral heatsink
- Suitable for warehouse, factory, gas station, workshop
- 160° beam angle is perfect for illuminating large spaces without leaving dark spots.
- 0-10V dimming.



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Watts	CCT	LM/Watt	Total LM	Voltage	Color
05819	PUCYWHI8	15W 20W	3500K 4000K 5000K	135 LM/W	2,025 LM 2,700 LM	120-277V	Bronze
05820	PGE00P5R	20W 30W 45W	3500K 4000K 5000K		2,700 LM 4,050 LM 6,075 LM		
05816	PUCYWHI8	15W 20W	3500K 4000K 5000K	135 LM/W	2,025 LM 2,700 LM		White
05817	PGE00P5R	20W 30W 45W	3500K 4000K 5000K		2,700 LM 4,050 LM 6,075 LM		
05818	PFZRFENB	40W	3500K	5,400 LM			
		50W 60W	4000K 5000K	6,750 LM 8,100 LM			



LED CANOPY GARAGE LIGHT (LEO GSR)

Description

Capable of being mounted in any soffit/canopy or even surface mounted. Great outdoor lighting fixture applicable to 160° beam angle is perfect for illuminating large spaces without leaving dark spots any industrial or commercial premise but most particularly for gas stations.

Features

- 0-10V dimming.
- Die cast aluminum with integral heatsink
- Suitable for warehouse, factory, gas station, workshop
- 160° beam angle is perfect for illuminating large spaces without leaving dark spots.
- 0-10V dimming.



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Watts	CCT	LM/Watt	Total LM	Voltage	Color
05823	S-01Y257	20W 40W 60W 80W	3500K 4000K 5000K	135 LM/W	2,700 LM 5,400 LM 8,100 LM 10,800 LM	120-277V	Bronze

ACCESSORIES

Order Code	Description	Size	Hole	Voltage
05880	Canopy Flat Plate	18x18	8x8 Square Hole	-
05882	Canopy Flat Plate	18x18	-	-
05883	Canopy Flat Plate	24x24	8x8 Square Hole	-
05884	Canopy Flat Plate	24x24	-	-
08361	Step Down Transformer	-	-	200-480V to 100-277V

LIGHTING CONTROLS

Order Code	Description
06247	LED PIR Fixture Mounted Control Simple On/Off 39FT 120-347V Type D Connector White
06246	LED PIR Fixture Mounted Control 3 in 1 39FT 120-347V Type D Connector White
06278	Remote Control 1 Scene Programming with LCD Display White
06261	BLE PIR Fixture Mounted (SkyFi Blu+) Occupancy Sensor w/ Daylight Harvesting 40ft 100-277V Type D
06265	BLE Fixture Mounted Node (SkyFi Blu+) 120-277V Type D (MES)

LIGHTING CONTROLS

Order Code	Description
06251	DC Powered 3 in 1 Indoor PIR Stand-Alone Control 40ft for 01 ZSR Fixtures
06278	Remote Control 1 Scene Programming with LCD Display White
06264	WH DC Powered BLE PIR (SkyFi Blu+) Occ Control w/ Daylight Harvesting White 40ft for 01 ZSR & Z10 Fixtures
06270	DC Powered BLE PIR (LightLinq) Occ Control w/ Daylight Harvesting White 40ft for All ZSR Fixtures



LED SMALL FLOOD LIGHT

Description:

The LED Small Flood is a high performance LED lighting solution designed with optical versatility and a slim, low profile design. Its rugged cast aluminum housing minimizes wind load requirements and features an integral, watertight LED driver compartment and high performance aluminum heat sinks.

Features

- Die-cast aluminum housing with prismatic lens
- Suitable for warehouse, factory, storage, pedestrian lighting

[Click Here For Full Spec](#)

Order Code	Description	Wattage	CCT	Voltage	Color	Mount	Lens
05351	LED Flood Light	15W	5000K	120-277V	Bronze	Yoke Mount	Type 5 Lens
05354	LED Flood Light	30W				Trunnion Mount	
05355	LED Flood Light	30W				Yoke Mount	
05358	LED Flood Light	50W				Trunnion Mount	
05357	LED Flood Light	50W				Yoke Mount	

Order Code	DLC Product ID	Mount	Watts	CCT	LM/Watt	Total LM	Voltage	Color
05364	PLGDFS8V5R4R	Knuckle	15W	3000K 4000K 5000K	123 LM/W	1,845 LM	120-277V	Bronze
05359	PL7924GEQU02	Knuckle	30W			3,690 LM		
05360	PL7924GEQU02	Trunnion	30W			3,690 LM		
05361	PL5YGQOT1SC9	Knuckle	50W			6,150 LM		
05362	PL5YGQOT1SC9	Trunnion	50W			6,150 LM		

ACCESSORIES

Order Code	Description	Height	Voltage	Color	Function
08361	Step Down Transformer	-	200-480V to 100-277V	-	-

LIGHTING CONTROLS

Order Code	Description
06451	Photocell Button Style 120V-277V UL Listed
09172	Photocell Swivel Style 120-277V SEB



LED FLOOD LIGHT (PUMA G)

Description:

This fixture provides quality and energy efficient lighting to outdoor sport courts, parking lots, hotels, warehouse and many more. Instant startup allows for easy installation and operation. Provides bright long last light with no humming or flickering. Eligible for rebates thanks to DLC certification.

Features:

- Photocell Ready
- Light is soft and uniform, safe to the eyes.
- Cast aluminum construction.
- Prismatic polycarbonate lens



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Watts	CCT	LM/Watt	Total LM	Voltage	Color
05346	S-XYQ8PV	25W	3000K 4000K 5000K	155 LM/W	3,875 LM	120-277V	Bronze
		45W			6,975 LM		
		60W			9,300 LM		
05347	S-Z092YU	60W			9,300 LM		
		80W			12,400 LM		
05348	S-E5L9C6	100W	15,500 LM				
		120W	18,600 LM				
		135W	19,375 LM				
		150W	23,250 LM				

Mounts

Order Code	Description	Wattage
05755	LED Area Light Slipfitter Mount	Bronze
05756	LED Area Light Arm Mount	
05757	LED Area Light Trunnion Mount	

Lighting Controls

Order Code	Description
06261	BLE PIR Fixture Mounted (SkyFi Blu+) Occupancy Sensor w/ Daylight Harvesting 40ft 100-277V Type D
06265	BLE Fixture Mounted Node (SkyFi Blu+) 120-277V Type D





LED AREA LIGHT (LION SSR)

Description:

Our slim design LED Area Light is built to withstand all climates and extreme temperatures. This fixture features our new ZSR sensor ready technology, allowing the ability to add an array of controls. The easy mount system includes your choice of slipfitter, arm mount, or trunnion mount. With a Type III distribution it delivers an oval light with a lateral width of 40 degrees that is projects outwards into the area being lit, perfect for large areas including parking lots and roadways.

Features:

- Die cast aluminum with powder coat finish. UV-stabilized polycarbonate lens
- Suitable for retail, parking lot poles, street lights
- 6KV surge protection



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Watts	CCT	LM / Watt	Total LM	Voltage	Color	Lens
05697	PNQD0CSJ	60W 75W 90W	5000K	141 LM/W	8,460 LM 10,575 LM 12,690 LM	120-277V	Black	Type III
05698	PQLNR6BY	120W 135W 150W		130 LM/W	15,600 LM 17,550 LM 19,500 LM		Black	
05699	PG9IPHDS	200W 220W 240W		140 LM/W	28,000 LM 30,800 LM 33,600 LM		Black	
05687	P4P4KMRP	120W 135W 150W		130 LM/W	19,500 LM 21,450 LM 24,050 LM		White	
05688	PG9IPHDS	200W 220W 240W		140 LM/W	28,000 LM 30,800 LM 33,600 LM		White	
05689	PTNRO6HD	260W 280W 300W		138 LM/W	35,880 LM 38,640 LM 41,400 LM		White	
05789	PNQD0CSJ	60W 75W 90W		141 LM/W	8,460 LM 10,575 LM 12,690 LM		Silver	
05790	PQLNR6BY	120W 135W 150W		130 LM/W	15,600 LM 17,550 LM 19,500 LM		Silver	
05791	PNQD0CSJ	200W 220W 240W		140 LM/W	28,000 LM 30,800 LM 33,600 LM		Silver	

MOUNT OPTIONS



Arm Mount



Slipfitter Mount



Trunnion Mount

Mounts

Order Code	Description	Color
05702	Shoebox Easy Arm Mount	Black
05701	Shoebox Easy Arm Mount	White
05792	Shoebox Easy Arm Mount	Silver
05705	Shoebox Easy Slipfitter Mount	Black
05704	Shoebox Easy Slipfitter Mount	White
05793	Shoebox Easy Slipfitter Mount	Silver
05708	Shoebox Easy Trunnion Mount	Black
05707	Shoebox Easy Trunnion Mount	White
05794	Shoebox Easy Trunnion Mount	Silver

ACCESSORIES

Order Code	Description	Wattage	Voltage
05712	LED Shoebox Shield 100W 150W	100W-150W	-
05713	LED Shoebox Shield 240W 300W	240W-300W	-
08360	Step Down Transformer	-	480V-277V

LIGHTING CONTROLS

Order Code	Description
05714	Blue Twist Lock Photocell 100-277V UL Listed
05715	Blue Twist Lock Photocell 480V UL Listed
06251	DC Powered 3 in 1 Indoor PIR Stand-Alone Control 40ft for 01 ZSR Fixtures
06278	Remote Control 1 Scene Programming with LCD Display White
06264	WH DC Powered BLE PIR (SkyFi Blu+) Occ Control w/ Daylight Harvesting White 40ft for 01 ZSR & Z10 Fixtures
06270	DC Powered BLE PIR (LightLinq) Occ Control w/ Daylight Harvesting White 40ft for All ZSR Fixtures

LED AREA LIGHT (WOLF GSR)

Description:

Offers bright, clear, and uniform illumination that enhances visibility and improves safety in outdoor spaces. Additionally, this LED area light is available in a range of customizable options such as selectable color temperatures and wattage levels, allowing users to tailor their lighting to their specific needs.



Order Code	DLC Product ID	Watts	CCT	LM/Watt	Total LM	Voltage	Color			
05970	S-G5836R	60W 80W 100W	3000K 4000K 5000K	155 LM/W	9,300 LM 12,400 LM 15,500 LM	120-277V	Bronze			
05971	S-WGK601	120W 135W 150W			18,600 LM 20,925 LM 23,250 LM					
05972	S-ERNBKM	200W 220W 240W			31,000 LM 34,100 LM 37,200 LM					
05973	S-AW6CQF	260W 280W 300W			40,300 LM 43,400 LM 46,500 LM					
05974	S-WGK601	120W 135W 150W			18,600 LM 20,925 LM 23,250 LM			277-480V		
05975	S-AW6CQF	260W 280W 300W			40,300 LM 43,400 LM 46,500 LM					
05980	S-WGK601	120W 135W 150W			18,600 LM 20,925 LM 23,250 LM					
05981	S-ERNBKM	200W 220W 240W			31,000 LM 34,100 LM 37,200 LM			155 LM/W	120-277V	Black
05982	S-AW6CQF	260W 280W 300W			40,300 LM 43,400 LM 46,500 LM					
05985	S-WGK601	120W 135W 150W			18,600 LM 20,925 LM 23,250 LM					
05983	S-ERNBKM	200W 220W 240W	31,000 LM 34,100 LM 37,200 LM							
05984	S-AW6CQF	260W	40,300 LM							
		280W 300W	43,400 LM 46,500 LM							
05984	S-AW6CQF	260W	40,300 LM	155 LM/W	120-277V	Silver				
		280W 300W	43,400 LM 46,500 LM							

Features:

- **Currently available in Bronze Only**
- No UV or IR in the beam.
- Easy to install and operate.
- Energy saving, long lifespan.
- Light is soft and uniform, safe to eyes.
- Instant start, NO flickering, NO humming.
- Green and eco-friendly without mercury.



[Click Here For Full Spec](#)

Mounts

Order Code	Description	Color
05755	Slipfitter Mount	Bronze
05756	Arm Mount	Bronze
05757	Trunnion Mount	Bronze
05758	Slipfitter Mount	White
05759	Arm Mount	White
05760	Trunnion Mount	White
05761	Slipfitter Mount	Black
05762	Arm Mount	Black
05763	Trunnion Mount	Black
05764	Slipfitter Mount	Silver
05765	Arm Mount	Silver
05766	Trunnion Mount	Silver



Arm Mount



Slipfitter Mount



Trunnion Mount

LIGHTING CONTROLS

Order Code	Description
05714	Blue Twist Lock Photocell 100-277V UL Listed
05715	Blue Twist Lock Photocell 480V UL Listed
06251	DC Powered 3 in 1 Indoor PIR Stand-Alone Control 40ft for 01 ZSR Fixtures
06278	Remote Control 1 Scene Programming with LCD Display White
06264	WH DC Powered BLE PIR (SkyFi Blu+) Occ Control w/ Daylight Harvesting White 40ft for 01 ZSR & Z10 Fixtures
06270	DC Powered BLE PIR (LightLinq) Occ Control w/ Daylight Harvesting White 40ft for All ZSR Fixtures

LED AREA LIGHT (PANTHER SR)

Description:

With its ultra-bright illumination, you can now enjoy a well-lit and safe parking area for your customers and employees. Invest in the best and see the difference in your space. Get your LED area light today!

Features:

- Shorting cap included.
- Instant start, no flickering or humming.
- Green, eco-friendly, no mercury.
- 6KV surge protection.



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Watts	CCT	LM/Watts	Total LM	Voltage	Color
05369	P28AWEYT	100W	5000K	140 LM/W	13,000 LM	120-277V	Bronze
05370	PHG7C9HC	150W			19,500 LM		
05371	P5GWBVYN	200W			26,000 LM		
05373	PKH7HA04	100W			13,000 LM	277-480V	
05374	S-ILFOT5	150W			19,500 LM		

When placing your, please use Order Code.

Mounts

Order Code	Description	Color
05724	Area Light Slipfitter Mount	Bronze
05725	Area Light Arm Mount	Bronze
05726	Area Light Trunnion Mount	Bronze
05727	Area Light Slipfitter Mount w/Junction Box	Bronze

LIGHTING CONTROLS

Order Code	Description
05714	Blue Twist Lock Photocell 100-277V UL Listed
05715	Blue Twist Lock Photocell 480V UL Listed
06251	DC Powered 3 in 1 Indoor PIR Stand-Alone Control 40ft for 01 ZSR Fixtures
06278	Remote Control 1 Scene Programming with LCD Display White

LED STREET LIGHT (COUGAR S)

Description:

Great addition to poorly lit areas. Fixture can be mounted directly to a wall, pole, or to a new or existing mounting arm. With its built in photocell, this fixture turns on automatically when the environment gets dark and turns off by itself with the first glimpse of daylight.

Features:

- Built in photocell.
- Die-Cast aluminum housing.
- Prismatic polycarbonate lens
- Suitable for barn, farm, yard, garage, security light, perimeter lighting



[Click Here For Full Spec](#)


Order Code	DLC Product ID	Watts	CCT	LM/Watt	Total LM	Voltage	Color
05372	S-E7IM91	150W 200W 240W	5000K	137 LM/W	20,550 LM 27,400 LM 32,880 LM	120-277V	Silver

Mounts

Order Code	Description	Color
05728	Light Base Mount	Silver
05792	Easy Arm Mount	
05793	Easy Slipfitter Mount	
05794	Easy Trunnion Mount	

LIGHTING CONTROLS

Order Code	Description
05714	Blue Twist Lock Photocell 100-277V UL Listed
05715	Blue Twist Lock Photocell 480V UL Listed
06251	DC Powered 3 in 1 Indoor PIR Stand-Alone Control 40ft for 01 ZSR Fixtures
06278	Remote Control 1 Scene Programming with LCD Display White
06264	WH DC Powered BLE PIR (SkyFi Blu+) Occ Control w/ Daylight Harvesting White 40ft for 01 ZSR & Z10 Fixtures
06270	DC Powered BLE PIR (LightLinq) Occ Control w/ Daylight Harvesting White 40ft for All ZSR Fixtures



LED BOLLARD LIGHT (GIRAFFE G)

Description

These stylish fixtures provide 360-degree illumination, enhancing safety and visibility in walkways and driveways. Plus, with energy-efficient LED bulbs, durable materials, and weather-resistant designs, they require minimal maintenance and can withstand the elements. Choose from a variety of styles and colors to complement your home or business.

Features

- 12W, 16W, 22W
- 3000K, 4000K, 5000K
- 120-277V
- Choice of housing color
- Design options: round, square, dome
- Anti-UV pc lens



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Wattage	CCT	LM/Watt	Total LM	Voltage	Color
04800	PGPGZOIT	12W 16W 22W	3000K 4000K 5000K	130 LM/W	1,560 LM	120-277V	Clear Bronze
04801	P2LKOU DL				2,080 LM		Clear Bronze
04802	PQZ6T5N4				2,860 LM		Clear White

ACCESSORIES

Order Code	DLC Model #
04803	LED Bollard Base Bronze w/ Mounting
04804	LED Bollard Base White w/ Mounting
04805	LED Bollard Mounting Hardware



LED POST TOP LIGHT (LEOPARD G)

Description:

This beautifully designed LED post top light provides a style that can be used for traditional and contemporary applications. Some models offer CCT Tunable functionality, allowing the ability to change the light color temperature from a natural white (4000K) to a daylight white (5000K), giving this light the capability to fit all application necessities. For convenience, the photocell feature offers a maintenance-free dusk to dawn operation.

Features:

- No UV or IR in the beam
- Easy to install and operate
- Energy saving, long lifespan
- Light is soft and uniform, safe to eyes
- Instant start, NO flickering, NO humming
- Green and eco-friendly without mercury



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Wattage	CCT	LM/Watt	Total LM	Voltage	Color
05898	PELB5J5P	50W	4000K 5000K	155 LM/W	7,750 LM	120-277V	Bronze
	PWV28P22	60W			9,300 LM		
	PDNX30DQ	75W			11,625 LM		
05899	S-FLC3OZ	100W	4000K 5000K	155 LM/W	15,500 LM	120-277V	Bronze
	P4PZ2B41	120W			18,600 LM		
	S-KROVZ7	150W			23,250 LM		

ACCESSORIES / MOUNTS (* to convert to area light)

Order Code	DLC Model #	Color
90458	Convert Area Light Base (Slipfitter, Arm, Trunnion)	Bronze
05755	Slipfitter Mount	
05756	Arm Mount	
05757	Trunnion Mount	

LIGHTING CONTROLS

Order Code	Description
05714	Blue Twist Lock Photocell 100-277V UL Listed
06261	BLE PIR Fixture Mounted (SkyFi Blu+) Occupancy Sensor w/ Daylight Harvesting 40ft 100-277V Type D
06265	BLE Fixture Mounted Node (SkyFi Blu+) 120-277V Type D



LED Sports Light (Coyote SSR)

Description:

Various degree beam angles available to push more of the light to the ground. The usable degree beam angle ranges from 20 to 120 degrees, ideal for higher installs like outdoor sport courts, warehouses, shipyards, and airports. This fixture has a separate 10KV surge protection device to help prevent power failure due to a surge. Can be customized for your specific needs with its six applicable wattages. The unit comes with an adjustable U bracket mount designed to allow the light to be angled up or down, depending on the focus of action.

Features

- 400W - 1,200W
- 5000K
- 120-277V, 480V
- 20, 30, 40, 60, 80, 120-degree beam angles
- 20KV Surge Protection



[Click Here For Full Spec](#)

Order Code	DLC Product ID	Watt	CCT	LM/Watt	Total LM	Voltage	Color
05954	S-EO1WFH	300W 400W 500W	5000K	155 LM/W	46,500LM 62,000 LM 77,500 LM	120-480V	Black
05955	S-6FPQGT	500W 600W 750W			77,500 LM 93,000 LM 116,250 LM		
05956	S-WKONP7	800W 1000W 1200W			124,000 LM 155,000 LM 186,000 LM		

Drivers * Driver sold separately, make sure to add appropriate driver.

Order Code	Description	Watt	Voltage
05957	LED Stadium Light (Coyote SSR) Driver	300W 400W 600W	120-277V
05959	LED Stadium Light (Coyote SSR) Driver	500W 600W 750W	
05961	LED Stadium Light (Coyote SSR) Driver	800W 1000W 1200W	
05958	LED Stadium Light (Coyote SSR) Driver	300W 400W 600W	277-480V
05960	LED Stadium Light (Coyote SSR) Driver	500W 600W 750W	
05962	LED Stadium Light (Coyote SSR) Driver	800W 1000W 1200W	

Lenses

Order Code	Description	Watt
05969	LED Stadium Light (Coyote SSR) 20 degree lens	600W 750W
05978	LED Stadium Light (Coyote SSR) 20 degree lens	1000W 1200W
05979	LED Stadium Light (Coyote SSR) 40 degree lens	1000W 1200W
05966	LED Stadium Light (Coyote SSR) 60 degree lens	400W 500W
05976	LED Stadium Light (Coyote SSR) 60 degree lens	600W 750W
05967	LED Stadium Light (Coyote SSR) 80 degree lens	400W 500W
05977	LED Stadium Light (Coyote SSR) 80 degree lens	600W 750W
05968	LED Stadium Light (Coyote SSR) 120 degree lens	400W 500W

Mounts

Order Code	Description	Watt
05963	LED Stadium Light (Coyote SSR) Slipfitter Mount	400W 500W
05964	LED Stadium Light (Coyote SSR) Slipfitter Mount	600W 750W
05965	LED Stadium Light (Coyote SSR) Slipfitter Mount	1000W 1200W

LIGHTING CONTROLS

Order Code	Description
06251	DC Powered 3 in 1 Indoor PIR Stand-Alone Control 40ft for 01 ZSR Fixtures
06278	Remote Control 1 Scene Programming with LCD Display White
06264	WH DC Powered BLE PIR (SkyFi Blu+) Occ Control w/ Daylight Harvesting White 40ft for 01 ZSR & Z10 Fixtures
06270	DC Powered BLE PIR (LightLinq) Occ Control w/ Daylight Harvesting White 40ft for All ZSR Fixtures



Mounting brackets and accessories for our Shoebox Lights can be found on pages 53.

Order Code	Description	Color	Mount Position
01002	Straight Wall Mount Bracket	Bronze	
01003	Straight Wall Mount Bracket	White	
01004	90° Degree Wall Mount Bracket	Bronze	L Bracket
01005	90° Degree Wall Mount Bracket	Black	L Bracket
01006	Side Mount Bracket for Square Pole	Bronze	
01100	4" Square Tenon Adapter	Bronze	Vertical Mount
01101	4" Square Tenon Adapter	White	Vertical Mount
01102	4" Circle Tenon Adapter	Bronze	Vertical Mount
01103	4" Circle Tenon Adapter	White	Vertical Mount
01104	4" Square Short Single Tenon	Bronze	Horizontal
01105	4" Square Short Single Tenon	White	Horizontal
01106	4" Square Short 180° Twin Tenon	Bronze	
01107	4" Square Short 180° Twin Tenon	White	
01108	4" Circle Short 180° Twin Tenon	Bronze	
01109	4" Circle Short 180° Twin Tenon	White	
01110	4" Square Short 90° Twin Tenon	Bronze	
01111	4" Square Short 90° Twin Tenon	White	
01112	4" Circle Short 90° Twin Tenon	Bronze	
01113	4" Circle Short 90° Twin Tenon	White	
01114	4" Square Short 90° Triple Tenon	Bronze	
01115	4" Square Short 90° Triple Tenon	White	
01116	4" Circle Short 90° Triple Tenon	Bronze	
01117	4" Circle Short 90° Triple Tenon	White	
01118	4" Square Short 90° Quad Tenon	Bronze	
01119	4" Square Short 90° Quad Tenon	White	
01120	4" Circle Short 90° Quad Tenon	Bronze	
01121	4" Circle Short 90° Quad Tenon	White	
01200	4" Square Low Profile 180° Dual Tenon	Bronze	
01201	4" Square Low Profile 180° Dual Tenon	White	
01202	4" Square Low Profile 180° Quad Tenon	Bronze	
01203	4" Square Low Profile 180° Quad Tenon	White	
01204	4" Square Low Profile 180° Triple Tenon	Bronze	
01205	4" Square Low Profile 180° Triple Tenon	White	
01250	4" Circle Bullhorn 180° Dual Tenon	Bronze	
01251	4" Circle Bullhorn 180° Dual Tenon	White	
01252	4" Circle Bullhorn 180° Triple Tenon	Bronze	
01253	4" Circle Bullhorn 180° Triple Tenon	White	
01254	4" Circle Bullhorn 180° Quad Tenon	Bronze	
01255	4" Circle Bullhorn 180° Quad Tenon	White	



LED EMERGENCY DRIVER

Our LED Emergency Driver provides constant power output to the load during emergency mode operation. It can be operated as NORMALLY-ON, NORMALLY-OFF, or SWITCHED LOAD. Included with a Charge/Power “ON” LED indicator light and push-to-test switch for mandated code compliance testing. This LED driver is suitable for installation inside, on top, or in remote mount of the fixture.



Order Code	Description	Wattage	Voltage	Lumens
06750	LED Emergency Driver	10.7W	20-50V DC	1600 LM
06752	LED Emergency Driver	13.7W	20-50V DC	2000 LM
06751	LED Emergency Driver	17W	20-50V DC	2400 LM

*Functions include occupancy sensor, bi-level dimming, and daylight control.

Order Code	Description	Height	Voltage	Color	Function
Fixture-Embedded Sensors (Indoor)					
06230	DC Powered 3 in 1 OcuSense Control For Sensor Ready Troffer	19ft	10-15 VDC	White	3-in-1*
06234	DC Powered 3 in 1 Indoor OcuSense Sensor For Sensor Ready Round High Bay	49ft	10-15 VDC	Black	3-in-1*
06243	DC Powered 3 in 1 OcuSense Control for Sensor Ready Magnetic Strips and Flat Panels	19ft	10-15 VDC	White	3-in-1*
06254	DC Powered 3 in 1 PIR Control for Sensor Ready Back-lit Panels and Troffer	19ft	120-347V	White	3-in-1*
06259	DC Powered 3 in 1 OcuSense for Ash-Pine-Lion-Full/Slim Cutoff Wall Pack	49ft	120-347V	Black	3-in-1*
Fixture-Mounted Sensors (Indoor)					
06221	LED OcuSense Fixture Mounted Control	19ft	120-277V	White	3-in-1*
06224	LED OcuSense Round High Bay Control	49ft	120-277V	Black	3-in-1*
06225	LED OcuSense Fixture Mounted Control	49ft	347-480V	White	3-in-1*
06227	LED OcuSense Round High Bay Control	49ft	347-480V	Black	3-in-1*
06246	LED PIR Fixture Mounted Control	39ft	120-347V	White	3-in-1*
06247	LED PIR Fixture Mounted Control	39ft	120-347V	White	Simple On/Off
06240	LED Daylight Harvesting Control	-	1-10 VDC	White	1-10V Dimmer / 10-100% Continuous Dimming
Remote Control					
06278	LED Intelligent Remote Control	-	-	White	LCD Display




*Functions include occupancy sensor, bi-level dimming, and daylight control.

LiteLink

Efficiency Linked



Wireless Bluetooth Wall Switch (MES)



[Click Here For Full Spec](#)

DC Powered BLE PIR Occ Control w/ Daylight Harvesting White 17ft For Quick Connect SR Fixtures (MES)



[Click Here For Full Spec](#)

Wireless Bluetooth Wall Switch



[Click Here For Full Spec](#)



LED PIR Fixture Mounted Occupancy Sensor W/Daylight Harvesting

[Click Here For Full Spec](#)



DC Powered BLE OcuSense Occ Control w/ Daylight Harvesting White 40ft for All ZSR Fixtures

[Click Here For Full Spec](#)

DC Powered BLE PIR Occ Control w/ Daylight Harvesting White 40ft for All ZSR Fixtures (MES)



[Click Here For Full Spec](#)



DC Powered PIR Occupancy Sensor for 06265


[Click Here For Full Spec](#)



Bluetooth Power Pack 100-277V

[Click Here For Full Spec](#)

DC Powered BLE Occ Control w/ Daylight Harvesting White 17ft For Quick Connect SR Fixtures (MES)



[Click Here For Full Spec](#)



DC Powered BLE PIR Occ Control w/ Daylight Harvesting White 40ft for All ZSR Fixtures (MES)

[Click Here For Full Spec](#)



FAN MOTORS



ANTI-SWEAT



STRIP CURTAINS



DOOR CLOSER



COOLER & VENDING MISERS

Order Code	Product
------------	---------

Fan Motors

08100	ECM Blue 3.3in Evaporator Fan Motor Straight Shaft 115V/208-230V CW/CCW
08101	ECM Blue 3.3in Evaporator Fan Motor Control w/ Thermistors (Controls up to 5 Motors) 08515
08102	ECM Blue Reach-In Motor Screw Shaft 115V/208-230V CW/CCW
08125	Wireless Programmer Kit for Azure Motor 08505
08127	Relay in a Box RIB01P

Anti-Sweat

08010	Relative Humidity Anti-Sweat Heater Control Kit
-------	---

Strip Curtains


08025	QuickStrip - Standard Smooth 8in x .080in x 8ft (1 Strip)
08026	QuickStrip - Standard Smooth 8in x .080in x 296ft (1 roll of 37 x 8ft Strips)
08027	QuickStrip Low Temp Non-Reinforced 8in x .080in x 8ft (1 Strip)
08028	QuickStrip Low Temp Non-Reinforced 8in x .080in x 296ft (1 roll of 37 x 8ft Strips)
08029	QuickMount MD 2FT Section of Mounting Hardware

Door Closers

08000	Light Commercial Door Closer
-------	------------------------------

Cooler & Vending Misers

08015	Cooler Miser with Sensor UL Listed
08017	Vending Miser with Sensor





LED V-SHAPE COLD CASE (COOLER) LIGHT

Description:

This 45° LED V-shape cold case (cooler) light with fixture bracket is ideally used for cooler lighting. The 45° V-shape design has a 160° beam angle that gives products a sharper look as more light shines towards them giving off a perfect 5000k natural white light. These LED lights contain no mercury and are in accordance with CE and RoHS testing standards, in addition to being ETL certified and come in 4', 5' and 6' variations.

Features:

- Aluminum polycarbonate lens
- Suitable for coolers, refrigeration, workshops, warehouses



[Click Here For Full Spec](#)

Order Code	Product	Size	Wattage	CCT	Voltage	Color	Lens	Function
08072	LED Cold Case (Cooler) Light	4ft	18W	6500K		White	Clear	Daisy Chain
08073	LED Cold Case (Cooler) Light	5ft	32W	5000K	120 - 277V	White	Clear	Daisy Chain
08074	LED Cold Case (Cooler) Light	6ft	40W	5000K		White	Clear	Daisy Chain



LED SPIDER GROW LIGHTS

Description:

Our full-cycle LED Spider Grow Lights are designed to target only the parts of the spectrum your plants need to thrive through both vegetative and flowering cycles. Continuous dimming (0-10V) comes standard. Suitable for use with dimmers and controllers. Multiple fixtures can be connected together using a single controller and then grouped together to be controlled simultaneously.

Features:


- Aluminum polycarbonate lens
- Suitable for coolers, refrigeration, workshops, warehouses



[Click Here For Full Spec](#)

MADE TO ORDER

Order Code	Description	Wattage	CCT	Voltage	Color	Lens	Beam Angle	Driver
02991	LED Spider Grow Light	330W	5000K	120-277V	Silver	Clear	120°	Sosen Driver
02993	LED Spider Grow Light	660W	5000K		Silver	Clear	120°	Sosen Driver





SOLAR MODULE

Description:
Solar modules convert sunlight to electricity via the photovoltaic effect. The high-power density solar modules yield great power per square meter, decrease labor installation time and decrease balance of system requirements. Dependent on the mounting application (roof or ground), the solar modules integrate various form factors and cell technologies: monofacial, bifacial, mono and poly.

- Features:**
- 30 year linear power warranty
 - 12 year product warranty on materials and workmanship
 - Heavy snow load up to 5400 Pa, wind load up to 2400 Pa
 - IEC 61730, UL 61730 certified
 - Suitable for ground mount and rooftop installations



Order Code	Product	Wattage	Cell Face	Cell Type	Manufacturer
09502	Solar Module	405	Bifacial	Poly	Canadian Solar



SOLAR INVERTER

Description:
Solar inverters convert direct current to alternating current in a photovoltaic system. The grid tied inverter are designed to provide high yield and enable significant balance of system savings. Dependent on system requirements, the inverter are either single phase or three phase. Conversion efficiency yields up to 98.8% and a wide operating range.

- Features:**
- 10 year standard warranty, available to extend up to 20 years
 - Maximum efficiency of 98.8%
 - UL 1741 & IEC 62109.1 certified for safety
 - IEEE 1547 & EC 62109.2 certified for safety & operability with utility grid
 - Monitoring for real-time operational efficiency



Order Code	Product	Rated AC Power	Manufacturer
09503	Inverter	60,000	Canadian Solar
09504	Wirebox	50,000-60,000	Canadian Solar



NOTES



PHONE

630.293.7338

GENERAL INFORMATION

MatrixLED Solutions Inc.com

WEBSITE

MatrixLED Solutions Inc.com